

AMERICAN SECURITY PRODUCTS COMPANY

Home Security Safes



Standard Features:

- Protect your important documents, cash and other valuables conveniently at home.
- Massive 3/4" steel door filled with fire insulating material.
- 1/8" formed steel body and door jamb for resistance to pry attacks.
- Seven 1" diameter chrome plated locking bolts secure a recessed door.
- Independent laboratory tested in a gas furnace at temperatures up to 1275°F, for a period of 30 min. Interior temperature did not exceed 350°F.
- Group II lock protected by drill resistant hard plate. Spy proof key locking dial provided on high gloss finishes and front read key locking dial provided on textured finishes.
- All safes come with plush velour interiors.
- Available in 7 high gloss and 4 textured finishes.



Interior temperature less than 350°F for a period of 30 min. at 1275°F.



2020-LT-GR

Model #	Inside Dimensions H x W x D	Outside Dimensions H x W x D*	Thickness Door Body	Total Bolts	Interior Shelves	Wt. Lbs.
2020-(1)-(2)	17½ x 18¼ x 16¼	20 x 20 x 20	3/4" 1/8"	7	1	150
3020-(1)-(2)	27½ x 18¼ x 16¼	30 x 20 x 20	3/4" 1/8"	7	2	225
4020-(1)-(2)	37½ x 18¼ x 16¼	40 x 20 x 20	3/4" 1/8"	7	3	325

(1) - Please specify hardware and trim package (see page 25 for hardware and trim options)

(2) - Please specify color (see page 25 for color options).

*Add 2" for handle, dial and hinge projection.



3020-LS-N-IY

"B/C" Rate Security Chests

AMSEC "B" and "C" Rate security chests are designed to provide secure storage at an economical price. In addition to meeting the requirements of The Insurance Offices Manual of Burglary Insurance, these units offer an appearance and many features similar to AMSEC's higher rated TL-15 models.

Standard Features:

Door:

- 1" ("C" Rate), or 1/2" ("B" Rate) steel pry-resistant recessed door.
- U.L. listed Group II key changeable lock, with relock and 1 million possible combinations.
- Additional spring loaded relocking device, activated by a punching attack.
- Locks and relocks protected by a large carburized hardplate.
- A handle activated locking mechanism consisting of three 1" chromed steel locking bolts. (five in BLB and BLC4024 models).

- Solid steel full length dead bar prevents door removal if hinges are removed during a forced entry attempt.
- Adjustable ball bearing hinges.

Body:

- 1/2" continuously welded ("C" rate) or 1/4" ("B" Rate) solid steel bodies.
- Body reinforcing frame gives the appearance of 1" thick walls to discourage attack.
- Adjustable shelves.
- Attractive Gray textured finish. Other colors available.
- Custom sizes, interior options and high security features available.
- Left swing door optional.



4020-LT-ST

Model No.	Inside H x W x D	Outside* H x W x D	Door Opening	Cubic Inch Capacity	Wt. Lbs	Interior Shelves
"B" Rate						
BLB2018	20 x 18 x 12	20½ x 18½ x 15	18 x 16	4,320	200	2
BLB3018	30 x 18 x 16	30½ x 18½ x 19	28 x 16	8,640	300	2
BLB3024	30 x 24 x 20	30½ x 24½ x 23	28 x 22	14,400	360	3
BLB4024	40 x 24 x 20	40½ x 24½ x 23	38 x 22	19,200	445	4
"C" Rate						
BLC2018	20 x 18 x 12	21 x 19 x 16	18½ x 16½	4,320	370	2
BLC3018	30 x 18 x 16	31 x 19 x 20	28½ x 16½	8,640	550	2
BLC3024	30 x 24 x 20	31 x 25 x 24	28½ x 22½	14,400	740	3
BLC4024	40 x 24 x 20	41 x 25 x 24	38½ x 22½	19,200	925	4

*Add 2" to outside depth for handle, dial and hinge projection. Extra shelves optional.



BLC3018