



AMERICAN SECURITY PRODUCTS COMPANY

“B” Rate Rotary and Front Loading Depository Safes



DSF2014
w/ ESL10 lock

DSF2714K



DSC2014KC

DSF3214CC

Reverse Hopper



DSR2014 with ESL-10



DST2731CC

AMSEC's DS series Depository safes are designed to provide immediate deposits and secure storage for cash, jewelry, and miscellaneous valuables. Deposits can be made through a locked door via a top-loading rotary hopper, a reverse hopper, or a front-loading deposit door.

FEATURES:

Body:

- Strong, formed "B" Rate construction made of A36 solid steel plate for improved security and appearance.
- Formed door jamb for increased resistance to sledgehammer attack.
- Four anchor bolt holes are standard.

Door: Model Number 2014 and 2714

- 1/2" thick A36 solid steel plate, recessed 1/2" to increase resistance to pry attack.
- U.L. Group II combo lock (C), U.L. listed dual nose keylock (K).
- Three 1" diameter chromed steel locking bolts.
- Bolt detent system engages boltwork automatically.
- Auxiliary spring-loaded reloading device.
- Lock and relock protected by large carburized hardplate.

(Additional features: Models #3214/2731)

- 3-way boltwork with 1" x 1/2" rectangular plated bolts.

Hopper:

- 2014/2714 are available w/ reverse hopper.
- Large package sizes: (Extra-large Rotary): 6-1/4"D x 5" W x 10-1/2"L (Front/Reverse Load): 4"D x 2"W x 9-3/4"L
- Recessed, heavy duty 3/16" construction (1/4" door).
- Protected by dual "anti-fish" baffles.

Additional Features: Wide Body Model (2731)

- Unique space-efficient, side-by-side design creates full depth depository and large storage compartment.
- Accepts cash trays up to 13" x 18".
- Optional coin rack available on storage compartment door.

IMPORTANT: AMSEC Depository safes are recommended for any operation that requires a non-returnable deposit such as armored car companies, convenience stores, restaurants, etc. These safes are not meant for overnight storage of cash or valuables.

Model No.†	Inside H x W x D	Outside H x W x D*	Door Opening	Cubic Inch Capacity	Wt. Lbs
DST2014	11 1/2 x 13 3/4 x 11	20 1/4 x 14 x 14	9 3/4 x 9 3/4	1,739	100
DSF2014	10 x 13 3/4 x 11	20 1/4 x 14 x 14	9 3/4 x 9 3/4	1,513	94
DSR2014	10 x 13 3/4 x 11	20 1/4 x 14 x 14	9 3/4 x 9 3/4	1,513	94
DSC2014KC**	(bottom) 10 x 13 3/4 x 11 (top) 6 5/8 x 13 3/4 x 12 5/8	27 1/4 x 14 x 14	(bottom) 9 3/4 x 9 3/4 (top) 6 x 9 1/2	1,513 1,127	118
DST2714	17 x 13 3/4 x 11	27 1/4 x 14 x 14	9 3/4 x 9 3/4	2,571	120
DSF2714	17 x 13 3/4 x 11	27 1/4 x 14 x 14	9 3/4 x 9 3/4	2,571	110
DSR2714	17 x 13 3/4 x 11	27 1/4 x 14 x 14	9 3/4 x 9 3/4	2,571	110
DST3214	(top) 11 x 13 3/4 x 11 (bottom) 12 1/2 x 13 3/4 x 11	32 1/4 x 14 x 14	9 x 8 1/2	1,664 1,890	152
DSF3214	(top) 9 1/2 x 13 3/4 x 11 (bottom) 12 1/2 x 13 3/4 x 11	32 1/4 x 14 x 14	9 x 8 1/2 9 x 8 1/2	1,437 1,891	144
DST2731	(left) 18 1/2 x 14 3/8 x 18 (right) 27 x 16 x 18	27 1/4 x 30 3/4 x 21	(left) 9 x 8 1/2 (right) 22 1/2 x 13	4,787 7,776	276
DSF2731	(left) 17 x 14 3/8 x 18 (right) 27 x 16 x 18	27 1/4 x 30 3/4 x 21	(left) 9 x 8 1/2 (right) 22 1/2 x 13	4,399 7,776	276

* Add 2" to outside depth for dial and handle projection.

†Specify Prefix: T=Top loading, F= Front loading, R=Reverse hopper.

Suffix: K=Keylock C=Combo lock.

** K=Camlock