

AMERICAN SECURITY PRODUCTS COMPANY



Wall Safes

AMSEC Wall safes are designed to provide hidden protection for documents and miscellaneous valuables. Each wall safe is also designed for easy installation between 16 o/c wall studs with pre-drilled anchor holes and a built-in flange eliminating unnecessary replastering.

Heavy-Duty WS1214 Features:

- 3/4" thick solid steel door, recessed for flush mounting.
- Heavy-duty "B" rate fully welded body construction.
- U.L. Group II combination lock with internal relock device (electronic lock optional)
- An additional spring loaded relocking device, activated by a punch attack.
- Locks and relocks protected by a large carburized hardplate.
- A handle activated locking mechanism consisting of five 3/4" diameter chrome steel locking bolts.
- One piece heavy-duty dead bar.
- One removable shelf.
- Extra deep interior.
- Attractive black finish with brass plated dial and gold emblem.

WS1014/WS1514 Features:

- U.L. listed Group II key changeable lock, with relock and 1 million possible combinations
- Electronic lock optional, or Chicago single key camlock with 2 keys.
- Flat dial allows flush mounted installation.
- 3/16" thick solid steel door with dead bar.
- Continuous non-removable hinge.

WES2113 Features:

- Offering excellent burglary protection with a heavy duty steel body, 1/4" solid steel door and flange.
- Extra spacious interior, while still offering the convenience of fitting between studs.
- Easy to use push button electronic lock offers solid protection with the accessibility of quick entry and easy-change combo.
- Standard key override, in case of lost combination.
- Dual live bolts ensure protection against pry attacks.
- Two removable shelves.
- Cream colored, durable powder coated finish.
- Packaged for UPS shipment.

When fire is a concern, there is no better wall safe than the WFS1310 or WES1310.

WFS1310 Features:

- 1 hour fire rating, insuring the inside temperature never exceeded 350° (paper chars at 450°)
- Extra deep interior, with a convenient pull-out tray.
- Three wheel changeable combination lock with knob operated locking mechanism.
- To fight against pry-attacks, each safe is equipped with side locking boltwork mechanism incorporating a large 1 1/8" rectangular steel locking bolt.
- Two 1 1/8" rectangular steel deadbolts, preventing door removal during a forced entry attempt.
- Impressive 5/8" thick door with attractive two-tone Sage finish.

WES1310 (with Electronic Lock) Features:

- Same outstanding features of the WFS1310 and comes equipped with an easy to operate electronic lock.
- Electronic lock offers high tech design with a 6 digit, easy change electronic keypad.



WS1214



WS1014



WS1514K



WES1310



WES2113

Model No.	Inside H x W x D	Outside H x W x D	Door Opening	Cubic Inch Capacity	Wt. Lbs	Interior Shelves
WS1014**	10 x 13 3/4 x 3 1/2	12 1/4 x 15 3/4 x 4	9 5/8 x 12 3/4	481	22	1
WS1514**	15 x 14 x 3 1/2	16 1/2 x 15 1/2 x 4	14 x 13 1/4	735	26	2
WS1214	12 x 13 1/2 x 5 1/2	12 5/8 x 14 1/8 x 10	10 3/4 x 11 1/8	891	86	2
WES2113	21 1/2 x 13 5/8 x 2 7/8	22 1/8 x 15 1/8 x 4 1/2	19 1/4 x 12	825	40	2
WFS1310*	13 1/4 x 9 5/8 x 9 1/2	17 x 13 x 14 5/8	13 1/4 x 9 5/8	1,149	81	1tray
WES1310*	13 1/4 x 9 5/8 x 9 1/2	17 x 13 x 14 5/8	13 1/4 x 9 5/8	1,149	81	1tray

* 350°F, one hour fire rated wall safe.

** Specify suffix - K = camlock