



High Security Tubular Key Locks

GEM 1000 Series Locks

7 Pin Tumbler

**STOCK
LOCKS**

MULTI-FUNCTION

Illustration	Number	Description	Box Qty.																
Cam Locks - Nickel Plated		KD, KA 27379, 27380, 27381, 27382, 27383, 27384, 27385																	
	• Multi-function																		
	MFW1038	1/2" 'A' Dimension	25																
	MFW1058	23/32" 'A' Dimension	25																
	MFW1078	15/16" 'A' Dimension	25																
	MFW1118	1- 5/32" 'A' Dimension	25																
	MFW1148	1-1/2" 'A' Dimension (Not Available Master Keyed)																	
Switch Lock - Momentary & Maintaining - Nickel		KD, KA 27379, 27380, 27381, 27382, 27383																	
	• Multi-function																		
	MFSW3-1138	Rekeyable Switch Lock - UL Rated Maintaining & Momentary Contact, Single Pole, Double Throw Switch, 125/250VAC 7A (Resistive Load) Lead Length 10" 'A' Dimension 1-3/8"	<table border="1"> <thead> <tr> <th colspan="4">Parts Provided For:</th> </tr> <tr> <th>Function</th> <th>Turn</th> <th>Key Removable</th> <th>Function</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>90° CW</td> <td>12 & 3</td> <td>Maintained</td> </tr> <tr> <td>2</td> <td>90° CW</td> <td>12</td> <td>Momentary Spring Back</td> </tr> </tbody> </table>	Parts Provided For:				Function	Turn	Key Removable	Function	1	90° CW	12 & 3	Maintained	2	90° CW	12	Momentary Spring Back
Parts Provided For:																			
Function	Turn	Key Removable	Function																
1	90° CW	12 & 3	Maintained																
2	90° CW	12	Momentary Spring Back																
Switch Lock - Maintaining - Nickel Plated		KD, KA 27379, 27380, 27381, 27382, 27383																	
	SW2-1138AD	Maintains Contact at 3:00 Single Pole, Single Throw Switch 110-120VAC, 7 Amps (Resistive Load) Key Removable At 12:00 & 3:00 'A' Dimension, 1-3/8" Lead Length 10"	10																
Switch Lock - Momentary - Nickel Plated		KD, KA 27379, 27380, 27381, 27382, 27383																	
	SW20-1138MC	Momentary Contact, Single Pole, Single Throw Switch 110-120VAC, 7 Amps (Resistive Load) Operation: 90° CW Turn Contacts Closed - Spring Back to 12:00, Key Removable 'A' Dimension, 1-3/8" Lead Length 10"	10																

All part numbers shown in red are available through the STOCK LOCKS program.